



# OPEN CHANNEL (WIRED FOR LED)

## FEATURES:

- IP20, 0,5mm steel powder-coated.
- Rota-lock lamp holders.
- 2 Amp inline fuse included in connector block.
- Wired for LED T8 configurations - L/N Live Neutral connection single-side

**BENEFITS:** IEC, NRCS approved

## T8 LED TECHNICAL DATA

| Product Code | Lamp Configuration | Qty/Ctn | Input Voltage | Dimensions L x B x H | PF                | IP Rating |
|--------------|--------------------|---------|---------------|----------------------|-------------------|-----------|
| DLC004       | 2*4ft LED Tube     | 10      | 220-240       | 1230mm*83mm*33mm     | LED Tube Specific | 20        |
| DLC006       | 2*5ft LED Tube     | 10      | 220-240       | 1532mm*82mm*33mm     | LED Tube Specific | 20        |

**DAYLIGHT**  
LIGHTING

PREMIUM LIGHTING FOR HOUSEHOLD,  
INDUSTRIAL & COMMERCIAL APPLICATIONS

Daylight Lighting (Pty) Ltd  
Distribution throughout South Africa and Africa

Offices in: Port Elizabeth (Head Office), Cape Town, Johannesburg, Durban and Bloemfontein  
Tel: +27 (0) 41 484 3330 | Web: [www.daylightlighting.co.za](http://www.daylightlighting.co.za) | Email: [sales@daylightlighting.co.za](mailto:sales@daylightlighting.co.za)