



# MOISTURE PROOF (WIRED FOR LED)

## FEATURES:

- IP 65 Dust and Moisture Proof fitting.
- Suitable for Underground car parks, cold rooms, freezer rooms (-20 degrees Celsius)
- Food preparation/packaging rooms.
- Wired for LED T8 Configurations - L/N Live Neutral Connection Single-Side
- Stainless steel clips, ABS Body, PS lens

**BENEFITS:** IEC, NRCS approved



**DAYLIGHT**  
LIGHTING

PREMIUM LIGHTING FOR HOUSEHOLD, INDUSTRIAL AND COMMERCIAL APPLICATIONS

## T8 LED Technical Data

| Product Code | Lamp Configuration | Clips           | Input Voltage | Dimensions L x B x H | PF                | IP Rating |
|--------------|--------------------|-----------------|---------------|----------------------|-------------------|-----------|
| 01x18w-led   | 1*2ft LED Tube     | Stainless Steel | 220-240       | 663mm*70mm*76mm      | LED Tube Specific | 65        |
| 01x36w-led   | 1*4ft LED Tube     | Stainless Steel | 220-240       | 1262mm*70mm*76mm     | LED Tube Specific | 65        |
| 01x58w-led   | 1*5ft LED Tube     | Stainless Steel | 220-240       | 1560mm*70mm*76mm     | LED Tube Specific | 65        |
| 02x18w-led   | 2*2ft LED Tube     | Stainless Steel | 220-240       | 663mm*100mm*76mm     | LED Tube Specific | 65        |
| 02x36w-led   | 2*4ft LED Tube     | Stainless Steel | 220-240       | 1262mm*100mm*76mm    | LED Tube Specific | 65        |
| 02x58w-led   | 2*5ft LED Tube     | Stainless Steel | 220-240       | 1560mm*100mm*76mm    | LED Tube Specific | 65        |

All LED fittings wired Live - Neutral, one end only With 2amp replacable fuse (As per SABS standards)