



PREMIER COASTAL G2

FEATURES:

- 304 Stainless bracket
- Aluminium Body - Corrosion resistant
- Suitable for coastal areas
- 1000mm Cable Length
- Large voltage operating range 185v - 265v
- Working temp: -20°C + 50°C
- Philips Led chips
- 110 lumens per watt



DAYLIGHT
LIGHTING

PREMIUM LIGHTING FOR HOUSEHOLD, INDUSTRIAL AND COMMERCIAL APPLICATIONS

PRODUCT	PRODUCT CODE	POWER	IP	LUMENS	FITTING SIZE	SURGE PROTECTION
	DLFLC30	30W	65	3300	169*140*29mm	2Kv
	DLFLC50	50W	65	5500	202*167*31mm	2Kv
	DLFLC100	100W	65	11000	260*225*34mm	2Kv
	DLFLC150	150W	65	16500	300*256*38mm	8Kv
	DLFLC200	200W	65	22000	345*291*38mm	8Kv
	DLFLC300	300W	65	33000	400*331*49mm	8Kv
	DLFLC500	500W	65	55000	535*455*60mm	8Kv

SHARED SPECS



EFFICIENCY

110lm/w



Ra (CRI)

≥80



PF

>0.9



VOLTAGE

185-265



ANGLE

90°



KELVIN TEMP

6500K
(daylight)

DAYLIGHT LIGHTING

PREMIUM LIGHTING FOR HOUSEHOLD,
INDUSTRIAL & COMMERCIAL APPLICATIONS

Daylight Lighting (Pty) Ltd
Distribution throughout South Africa and Africa

Offices in: Port Elizabeth (Head Office), Cape Town, Johannesburg, Durban and Bloemfontein
Tel: +27 (0) 41 484 3330 | Web: www.daylightlighting.co.za | Email: sales@daylightlighting.co.za

*See product warranty terms and conditions at <https://daylightlighting.co.za/warranty-terms-and-conditions/>